
ARTICLE CODE	DESCRIPTION
SLB-8003	Sleeve box 653l - 1200x800x934mm - 3 skids - with flap door

BRAND

Cabka

PRODUCT DESCRIPTION

Collapsible container with M-fold sleeve with lid and pallet on 3 runners
Includes holders that keep the sleeve in place, even when the sleeve box is tilted
Due to the folding of the Sleeve Boxes there is a volume reduction of 75%
Maximum stacking depending on the filling weight of the sleeve boxes
Maximum 6 fully unfolded Sleeve Boxes of 250 kg can be stacked on top of each other
With a max filling weight of 500 kg a maximum of 3 fully unfolded Sleeve Boxes can be stacked on top of each other
Maximum load capacity static: max 1500 kg stacked
Maximum load capacity dynamic: max 750 kg
Maximum load capacity in racking: max 750 kg
Smooth inner walls ensure easy cleaning
Perfectly stackable, both unfolded and folded
Equipped with ergonomic handles in the lid for extra stability
Labelling possible
Colour collar: grey; lid and pallet: black
Suitable for automotive industry, pharmaceuticals (distribution), transport of samples & specimens, webshop logistics, ...
Including 1 drop door on the long side
Int. dim.: L1156 x W756 x H747 mm
Dim. folded: L1200 x W800 x H232 mm



SPECIFICATIONS

Length (mm)	1200
Width (mm)	800
Height (mm)	934
Net weight (kg)	40
Matter	• Polyethylene • Polypropylene
Color	Grey

TECHNICAL DETAILS

ETIM	EC004736
MOQ sales (Set)	1

ATTRIBUTES

Type	Sleeve box
Model	On 3 skids
Type Of Handles	Ergonomic handles in the lid
Quantity Handles	4
Label Holder	false
Load Capacity Static (kg)	1500
Food safe certified	false
Load Capacity Dynamic (kg)	750
Quantity Hinges	6
Load Capacity In Rack (kg)	750
Personalisation	false
Side Flap Door	Long side
Suitable For Liquids	false
Lid Included	true
Height Flap Door	300
Width Flap Door	400
Quantity Skids	3
Anti-slip cams included	true
Flap door included	true
Quantity flap doors	1
Stacking edges included	false
Folded height (mm)	232
Internal height (mm)	747
Internal length (mm)	1156
Internal width (mm)	756
% space saving when folded	75
Maximum quantity par stack	6
Type of bottom design	Closed
Type of side design	Closed
Type of side features	M-fold sleeve – Density 3000 g/m^2
Type of skids	Fully closed