ARTICLE CODE	DESCRIPTION
PPP-5610	Pallet Solid line - 1140x1140x165mm - open deck - 6 skids - recycled PO

BRAND

Cabka



PRODUCT DESCRIPTION

Reusable pallet suitable for long-term use
Impact-resistant material - without metal reinforcements
Universal, durable and environmentally friendly solution for storage, distribution, closed loops or export, pharmaceuticals & laboratory, healthcare sector, etc.
Suitable for intensive use in high-rotation logistics, semi-hygienic environments
Temperature resistant from -20°C to +40°C, cleaning up to +65°C (max. 10 min.) and short-term surface steaming up to +100°C
Weather and UV resistant
Easy cleaning
Rounded impact zones reduce risk of damage to a minimum
Raised edges ensure optimal transport security and stability
Options: anti-slip structures, customisation, etc.
100% recyclable at end of life
Entry height long side, between runner and deck: 95 mm
Maximum static load: 5000 kg
Maximum dynamic load: 2500 kg
Maximum racking load: 1375 kg
Packaging: 15 pallets/stack

SPECIFICATIONS

Length (mm)	1140
Width (mm)	1140
Height (mm)	165
Net weight (kg)	28.5
Matter	Polyolefins
Color	Anthracite

TECHNICAL DETAILS

ETIM	EC004004
MOQ sales (Pc.)	15

ATTRIBUTES

Model	Solid line
Gs Certificate	false
Quantity Par Stack	15
Load Capacity Static (kg)	5000
Load Capacity Dynamic (kg)	2500
Type Of Surface	Open deck
Nestable	false
Load Capacity In Rack (kg)	1375
Entry Height	Entry height between the runner and the deck: 95 mm //
Quantity Skids	6