
ARTICLE CODE	DESCRIPTION
PPC-8310	Pallet Solid line - 1200x800x157mm - closed deck - 3 skids - recycled

BRAND

Cabka

PRODUCT DESCRIPTION

Reusable pallet suitable for long-term use
Impact-resistant material - without metal reinforcements
Universal, durable and environmentally friendly solution for storage, distribution, closed loops or export, pharmaceuticals & laboratory, healthcare sector, etc.
Suitable for intensive use in high-rotation logistics, semi-hygienic environments
Temperature resistant from -20°C to +40°C, cleaning up to +65°C (max. 10 min.) and short-term surface steaming up to +100°C
Weather and UV resistant
Easy cleaning
Rounded impact zones reduce risk of damage to a minimum
Raised edges ensure optimal transport security and stability
Options: anti-slip structures, customisation, etc.
100% recyclable at end of life
Entry height short side: 116 mm
Entry height between runner and deck: 91 mm
Maximum static load: 6000 kg
Maximum dynamic load: 2500 kg
Maximum racking load: 1100 kg
Packaging: 15 pallets/stack



SPECIFICATIONS

Length (mm)	1200
Width (mm)	800
Height (mm)	157
Net weight (kg)	19
Matter	Recycled polypropylene
Color	Anthracite

TECHNICAL DETAILS

ETIM	EC004004
MOQ sales (Pc.)	1

ATTRIBUTES

Model	Solid line
Gs Certificate	false
Quantity Par Stack	15
Load Capacity Static (kg)	6000
Load Capacity Dynamic (kg)	2500
Type Of Surface	Closed deck
Nestable	false
Load Capacity In Rack (kg)	1100
Entry Height	Entry height short side: 116 mm // Entry height long side, between the runner and the deck: 91 mm //
Quantity Skids	3